

HSF

NOTES:

- Current Rating: 7.0AMP
- Contact Resistance: 30mΩ Max
- Withstand Voltage: 1000V AC/DC
- Insulation Resistance: 1000MΩ Min
- Operation Temperature: -40°C to +105°C
- Contact Material: Phosphor Bronze
- Contact plating: Sn over Ni
- Insulator Material: LCP+30%G.F UL94V-0

Ordering Information

2989 - 1 XX S XX DUN T 1

No. of Pins per Row: 02-40PIN
 Contact Plating: SN=Tin
 SM=Match Tin
 Packing: T=Tube

Item	Pitch	Mating
Standard	5.08	1925
Alternate		

REV	DATE	MODIFICATION DESCRIPTION
A0	2012/08/15	NEW

OPERATION	±0.40	DRAW	JYHuang	DATE	2012/08/15	SCALE	FIT	PART NO.	2989-1XXSXXDUNT1
XX	±0.25	CHECK		DATE		mm		TITLE:	PH: 08 SINGLE ROW 180° DIP H=8.9
X.XXX	±0.15	APPROVE		SHEET	1/1	A4		Customer NO.	
Angle	± 3'	PROJ.							

WCON
 Http: www.wcon.com
 WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com
 WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: sales@wcon.com

